DC BATTERY BACKUP WALL MOUN WI-FI® GARAGE DOOR OPENER

The ultimate garage access solution, designed to optimize space.



MyQ® Technology makes this opener compatible with multiple home automation platforms, including:







SMART

SPACE-SAVING DESIGN OPENS UP THE CEILING.

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MYQ REMOTE LED LIGHT PROVIDES BRIGHT, MAINTENANCE-FREE ILLUMINATION.

INCLUDED AUTOMATIC GARAGE DOOR LOCK MAKES THE GARAGE DOOR VIRTUALLY IMPENETRABLE.

MyQ MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE.**

QUIET AND RELIABLE

WALL-MOUNT DESIGN AND QUIET DC MOTOR ELIMINATE NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDE SMOOTH OPERATION.

HEAVY-LIFTING POWER OPERATES DOORS UP TO 850 LBS.

INTEGRATED BATTERY BACKUP ENSURES ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

SECURE

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

SECURITY+ 2.0° SENDS A NEW CODE WITH EVERY REMOTE CLICK.

MOTION DETECTOR AUTOMATICALLY TURNS ON THE LIGHT.

THE PROTECTOR SYSTEM® AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

*Linking your MyQ account to a partner may require an additional accessory purchase or subscription fee.

**MyQ Remote LED Light must be installed to enable use of Timer-to-Close or MyQ smartphone control of the garage door. See User Guide for additional information.

†Battery Backup must be installed. Must use 15" or greater radius track. Door must be properly balanced. Smartphone not included

PRODUCT GUIDE 8500W DC BATTERY BACKUP WALL MOUNT WI-FI GARAGE DOOR OPENER

INCLUDED ACCESSORIES:

MVQ REMOTE LED LIGHT

Operates automatically with the opener and works with the MyQ App.



INTEGRATED BATTERY BACKUP

Powers up the opener when the power's out.



AUTOMATIC GARAGE DOOR LOCK

Deadbolts the garage door automatically every time it closes.



SMART CONTROL PANEL®

LCD display enables simple programming and adjustment of settings



3-BUTTON REMOTE CONTROL

Operates up to 3 openers or MyQ Light Accessories



POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.







485LN

827LN

880LMW 893MA

WI-FI® GARAGE DOOR OPENER

MASTERFUL ENGINEERING.

MOTOR



- Heavy-Duty 12V DC

- Automatic Thermal Protection

- Permanent Lubrication

POWER -



- -120V AC
- 60 Hz Voltage
- -1.5A Current Rating
- UL® Listed
- -6' Power Cord (3-Prong)

MECHANICS -



- -Steel Chassis and Plastic Cover
- -Internal Chain and Sprocket Drive Mechanism

(63:1 Gear Reduction)

- Auto-Force Adjustment for Changing Weather and Environmental Conditions
- Electronic Limits for Easy Setup
- -DC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050DCRJWF)
- -2 Lock Terminals Allow Another Lock to Be Added for Extra Security (2 Max.)



DIMENSIONS

Max. Door Size: 14 ft.

Headroom Clearance Required: 3 in. from Center of Torsion Bar

> MAX. DOOR WEIGHT 850 lbs.[†]

8.5"

Per second for door to move upward

7.6" Per second

SPEED

for door to move downward

STANDARD SPECS.

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200

Operating Temperature: -31°F to 149°F

3-Button Remote Control (893MAX)

- -Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding
- *Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

Smart Control Panel® (880LMW)

- Timer-to-Close
- Program Remote Controls, Keypads and MyQ Accessories
- Maintenance Alert System
- Easy Wi-Fi Setup

MvQ® RADIO



- Provides 2-way communication from garage door opener and MyQ accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.**
- **MyQ Remote LED Light must be installed to enable use of Timer-to-Close or MyQ smartphone control of the garage door. See User Guide for additional information.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER***)

May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

LIGHTING

MyQ REMOTE LED LIGHT (8271 M)



- Multiple Programming Options, Including MyQ App Control
- Mounts to Ceiling or Wall
- Easy-to-Clean Hinged Cover

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTONS (1)

CARTON 1: 27.88" x 11.61" x 9.79"

- Garage Door Opener Head (8500W)
- Smart Control Panel (880LMW)
- -3-Button Remote Control (893MAX)
- -The Protector System® Safety Reversing Sensors
- Battery (485LM)
- Automatic Garage Door Lock (841LM)
- MyQ Remote LED Light (827LM)

SAFETY AND SECURITY.

- Automatic Garage Door Lock Included (2 Max.)
- Alert-2-Close/Unattended Close Operation^{††}
- Motion Detection Feature on Control Panel
- Hands-Free Work Lights On
- Emergency/Quick Release
- Ventilation/Pet Opening

- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls. 4 Wireless Keyless Entry Systems and 16 MyQ Devices

© 2017 LiftMaster All Rights Reserved 300 Windsor Drive, Oak Brook, IL 60523


LiftMaster.com

Copyright © 2000-2017, Alarm.com. All rights reserved. Alarm.com and the Alarm.com Logo are registered trademarks of Alarm.com

Apple® and iPhone® are registered trademarks of Apple Inc. HomeKit is a trademark of Apple Inc. © 2017 Google Inc. All rights reserved. Google Assistant is a trademark of Google Inc. Nest® and the Works with Nest logos are trademarks licensed by Nest Labs, Inc. Wi-Fi® is a registered trademark of Wi-Fi Alliance XFINITY Home and the XFINITY Home design logo are trademarks or service

marks of Comcast Corporation. UL® and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved. HomeLink® and the HomeLink House® logo are registered trademarks of Gentex Corporation LMGDENPG8500W 3/18





[†]Rattery Backup must be installed. Must use 15" or greater radius track. Door must be properly balanced. **Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended Close Operation features when installed with a sectional door.